

ACRIL-M S 6755

ACRYLICS

Medium Soft Acrylic Binder of fine particle size, provides good filling, adhesion and better dry / wet rub fastness properties to the finish.

CHARACTERISTICS OF EMULSION

Appearance	: Creamish Yellow Emulsion
Nature	: Polyacrylate Dispersion
Solid Content	: 36 ± 1%
pH (10% Sol.)	: 7.0 ± 0.5
Charge	: Anionic
Mechanical Stability	: Very Good
Reaction with Ammonia	: Increase in Viscosity

CHARACTERISTICS OF FILM

Appearance	: Transparent
Elongation	: 04 (1 Min. – 10 Max.)
Gloss	: 10 (1 Matt – 10 Glossy)
Shore Hardness	: 05 (1 Softest – 10 Hardest)
Light Fastness	: Good
Cold-crack Resistance	: Good

ACRIL-M S 6755 is versatile medium soft binder and can be used extensively for the finishing of various type of leathers.

ACRIL-M S 6755 provides good coverage and body to the finish.

Leather finished with **ACRIL-M S 6755** exhibit better fastness to rubbing and are smoother and uniform in look.

ACRIL-M S 6755 has good plate release and printing properties.

ACRIL-M S 6755 may be used alone or may be combined with other acrylic binders provided they are not cationic in nature.

ACRIL-M S 6755 is mostly compatible with the anionic auxiliaries normally use in leather finishing.

SUGGESTED APPLICATIONS:

Corrected Grain	:	150 parts	Pigment - Nano Series		
		150 parts	ACRIL-M S 6755		
		100 parts	Acril-m X79/60		
		50 parts	Filler WTD		
		50 parts	Filler 12/61		
		50 parts	Glaze Top EC		
		50 parts	Urez 894		
		400 parts	Water		
		Sheep Nappa	:	80 parts	Pigment - Nano Series
				100 parts	ACRIL-M S 6755
100 parts	Acril-m S 8/1				
30 parts	Filler 50				
30 parts	Glaze Top N				
20 parts	Luber 205				
50 parts	Urez 899				
590 parts	Water				

IMPORTANT: PROTECT FROM FREEZING

Note : Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.