

HICALAC MATT

Characteristics of Emulsion

Appearance	: Milky White Emulsion
Nature	: NC Emulsion
Solid Content	: $16 \pm 1\%$
pH (1:1)	: $7.5 \pm 0.5\%$
Flexibility	: Medium
Film Hardness	: Medium

REACH COMPLIANT



Green-Trek- Compliant

A symbol of our commitment to sustainable technologies

Storage : Store between +5 °c to 35 °c in original pack, well-sealed & stored.
Shelf-life : Product is stable for 6 months from the date of production / Invoice.



Non flammable

Avoid direct contact with skin



Store in dry place

Use Gloves / Ensure Ventilation



Nitrocellulose lacquer emulsion with a matting effect. Gives a matt or silky matt finish for clothing and shoe upper leathers. DOP/ DBP free.

HICALAC MATT is a water dilutable top coat used as a final matt finish. It imparts a smooth and uniform matting effect with a warm, soft and natural handle. Leathers finished with Hicalac Matt can be dry milled and will have good wet and dry rubbing resistance which can be controlled by dilution ratio.

HICALAC MATT can be mixed with other emulsion lacquers like Hicalac 316, Hicalac 312 or Aquasol W 100 in desired ratio to get different degrees of gloss on leather. Auxiliary products like Finish M 11, Finish M 45, Wax 16/S etc. may also be added to Hicalac Matt for modifying surface feel of the leather.

Usage

Stir before use 

Matt Top Coat	:	100	parts	Hicalac Matt
		50-100	parts	Water
Silky Gloss	:	50	parts	Hicalac Matt
		50	parts	Hicalac 316
		100	parts	Water

Note: Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.