

LUBER 205

LUBER 205 is a water based penetrating agent.

PROPERTIES:

Appearance	: Transparent Watery Liquid
Base	: Ester Tensides
Solid Content	: 5 ± 1%
pH (10% Sol.)	: 5.0 ± 0.5
Specific Gravity	: 0.95
Smell	: Ammonical Free
Shelf Life	: Six months

LUBER 205 is mostly compatible with usual finishing products and is specially designed to avoid irritating fumes during finishing operations. The product finds its main use as driving agent in the impregnating formulation for corrected grain leathers. It may also be used in spray dyeing for varying depth and penetration.

LUBER 205, if incorporated in covering formulations, helps in improving the anchorage of the resultant finish. It is always better to dilute the product with water before adding to the impregnating resin binders or season mix.

SUGGESTED APPLICATIONS:

Spray Dyeing	:	50 parts	LUBER 205
		100 parts	Dye Solution - Novolene Series
		850 parts	Water
Impregnation	:	100 parts	LUBER 205
		600 parts	Water
		250 parts	Acril-m Y 93
OR	:	50 parts	LUBER 205
		650 parts	Water
		300 parts	Acril-m Y 62
Season	:	100 parts	Pigment - Nano Series
		40 parts	Wax 16/S
		30 parts	Glaze Top N
		550 parts	Water
		100 parts	Acril-m X 858
		100 parts	Acril-m S 8/1
		30 parts	LUBER 205
		50 parts	Urez 899

PULLUP
OILS &
AUXILIARIES

Note : Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.