

**MODIFIER AM**

**Extremely versatile feel modifier and sealing agent of neutral nature for snuffed leather, splits or for upgradation of lower selections.**

**PROPERTIES:**

<b>Appearance</b>	: Creamish Thick Paste
<b>Nature</b>	: Waxy and Soapy
<b>Solid Content</b>	: 17 ± 1%
<b>pH (10% Sol.)</b>	: 8.5 ± 0.5
<b>Flexibility</b>	: Good
<b>Charge</b>	: Anionic
<b>Shelf Life</b>	: Six months

**MODIFIER AM** is a good additive for use in acrylic finishing for making the finish soft. It's application reduces over absorption of finish. This property renders it as a special additive in split finish and defect covering of lower selections. Leather finishes containing **MODIFIER AM** have smooth soft touch.

**MODIFIER AM** also has application as anti-sticking agent in the production of heavily embossed leathers.

**MODIFIER AM** should be dissolved in hot, soft water, normally used in leather finishing before adding it to the season mixture.

**SUGGESTED APPLICATIONS:**

For sealing of split or corrected grain leather, 50 - 100 gram of **MODIFIER AM** is diluted with one liter of water and sprayed. After complete drying, such leathers are plated at 90°C - 300 kg/cm<sup>2</sup> for better sealing.

In the finishing of softy upper and lower grades of garment leathers, normally 30-60 g/ltr of **MODIFIER AM** is used in season. It is advisable to use suitable quantity of Luber 205 along with **MODIFIER AM** for better adhesion of finish.

**MODIFIER AM** normally should not be used in glazed or polished finishes.

<b>Corrected Grain</b>	:	100	parts	Pigment - Nano Series
		100	parts	Acril-m S 60
		100	parts	Acril-m S 8/1
		100	parts	Urez 899
		30	parts	<b>MODIFIER AM</b>
		30	parts	Modifier WS
		40	parts	Filler 12/61
		50	parts	Protop 18
		450	parts	Water

FILLERS/  
WAXES/  
MODIFIERS

**Note :** Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.