

**PULLOL 411**

**PULLOL 411 is an oil based product in solvent medium for pull-up finish with dry touch.**

**PROPERTIES:**

<b>Appearance</b>	: Amber Coloured Liquid
<b>Nature</b>	: Synthetic and Natural Oils in Solvent Medium
<b>Solid Content</b>	: 92 ± 1%
<b>pH</b>	: N.A.
<b>Shelf Life</b>	: Six months

**PULLOL 411** is a solvent solution of synthetic and natural oils which imparts good pull up effect when applied to full grain or on slightly snuffed leathers.

**PULLOL 411** effectively produces a good pull up effect on hard to wet leathers. It is characterised by its good filling, masking and softening properties.

**PULLOL 411** is applied either as such or by diluting it with solvents like ethyl cellosolve with the help of roller coating machine. The treated leather must be aged at least for 12 hours and plated before further coating wherever a second coat is necessary.

After complete drying and proper ageing leathers coated with **PULLOL 411** in this manner should be plated at 100°-120°C/50 bar or Finiflexed at 130°C with minimum pressure to achieve darkened leather, having good pull up effect and fairly pleasant touch.

The leathers coated with **PULLOL 411** may also be finished with carefully prepared seasons of Glaze Top N (25-30 g/ltr. with water) followed by fixing with cross linking agents. Passing through contilux will result in pleasant handle and good gloss.

**PULLOL 411** has its characteristic odour but leather produced with it does not give pungent or bad smell even on prolonged ageing.

**SUGGESTED APPLICATION:**

**For Oil Pull-up Effect :** Direct roller coat (on snuffed leather). Air off over night, kiss plate, spray one cross coat, air off, contilux at 125°C/50 bar. Finish as required.

PULLUP  
OILS &  
AUXILIARIES

**Note :** Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.