

HARYANA

UPHOL UF 60

Low fogging, synthetic sperm based sulphited fatliquor of good heat, light fastness values for automotive upholstery and contains special tensides and antioxidants.

CHARACTERISTICS:

Appearance	: Brown Liquid
Base	: Sulphited Synthetic Sperm Substitute
Active Content	: 60 ± 1%
pH (1 : 10)	: 8.0 ± 0.5
Charge	: Anionic
Stability	: Good
Light Fastness	: Excellent

UPHOL UF 60 is a special fatliquor designed for high performance leathers like automotive / furniture upholstery but can also be used as general purpose fatliquor for all types of soft leathers.

Outstanding gravimetric & reflectometric fogging values, high heat / light fastness and ageing properties make **UPHOL UF 60** an ideal choice for automotive leathers. It provides excellent internal lubrication, good filling, roundness and suppleness to the treated leathers. It confers a warm pleasant touch and fine milling pattern to the leather grain.

EMULSION INSTRUCTIONS:

To the required quantity of **UPHOL UF 60**, or the fat mix, add 3-4 times the quantity of water at 60 - 70 °C under constant stirring.

SUGGESTED APPLICATIONS:

a) Automotive Upholstery	Fatliquoring	6.0 % UPHOL UF 60 8.0 % Uphol CN 4.0 % Uphol L 29
b) Cow Softy	Fatliquoring	3.0 % UPHOL UF 60 4.0 % Nouvol PK 2.0 % Maradol C
c) Sheep Nappa	Fatliquoring	4.0 % UPHOL UF 60 4.0 % Nouvol LS 55 3.0 % Maradol C 4.0 % Nouvol PK
d) Cow Nappa	Fatliquoring	6.0 % UPHOL UF 60 4.0 % Nouvol LS 55 2.0 % Maradol C 4.0 % Nouvol PK 2.0 % Uphol MK

LIGHT-WEIGHT FATLIQUORS

The product may show separation on prolonged storage or under extremes of temperature. However, this can be rectified, in most cases, by mixing thoroughly by stirring before use. Under normal conditions the product has a shelf life, in the unopened original container, of approximately 1 year.

Note : Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.