

WAX 16/S

WAX 16/S is an anti-gluing agent based on special waxes, proteins and silicones in aqueous medium & is used for high quality finishes.

PROPERTIES:

Appearance	: Off White Viscous Liquid
Nature	: Waxes, Proteins & Silicones
Solid Content	: 15 ± 1%
pH (10% Sol.)	: 9.0 ± 0.5
Flexibility	: Good
Shelf Life	: Six months

WAX 16/S can be used in resin seasons to eliminate tackiness. It improves the uniformity of finishing and imparts a soft and pleasant touch. The product has good filling and easy plating properties.

WAX 16/S with 40-80 g / litre of resin finish, produces silky waxy touch.

WAX 16/S (100 parts) if mixed first with 50 parts of Modifier CA/2 and then with water 850 parts and sprayed on leather as top coat produces waxy silky touch.

WAX 16/S (100 parts) if mixed first with 75 parts of Modifier WS and then with water 825 parts and sprayed on leather as top coat results in leather having more waxy and slightly silky feel.

WAX 16/S if mixed (40-80 parts) in season produces “easy plate release characteristics” with waxy touch.

FILLERS/
WAXES/
MODIFIERS

SUGGESTED APPLICATION:

Season Coat	:	100 parts	Pigment - Nano Series
		120 parts	Acrl-m X 858
		80 parts	Acrl-m S 8/1
		50 parts	WAX 16/S
		100 parts	Urez 898
		50 parts	Glaze Top N
		500 parts	Water

Note : Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.