

REPALLON SRW

Characteristics

Composition	: Water Insoluble Amino Silicon
Appearance	: Oily Liquid
Active Content	: 99 ± 1%
pH	: N.A.
Emulsions	: Water Insoluble
Light Fastness	: Good

Anionic, Siliconic Additive to enhance water repellence.

REPALLON SRW is specially designed to boost the action of water repellents, when combined with other hydrophobic and water repellent fatliquors. When used with Repallon ESW, it greatly improves the Bally and Maeser test values and spotting resistance of leather.

REPALLON SRW also enhances the brightness of dyeing and imparts silky touch & brightness to the treated leather. It is a lightfast, synthetic compound and does not produce white spots on leather. It may also be applied on crust as such or diluted with Isopropyl Alcohol (1:4) with normal coating techniques like roller or curtain coater.

Usage

Caution: 10-50% of REPALLON SRW by weight of total fatliqour can be safely used in the aqueous float. However, this quantity may vary depending upon the requirement and dispersing power of accompanying fatliquors.

Suggested Application

- ✓ Additive to Hydrophobic and Waterproofing Fatliquors

REACH COMPLIANT



Green-Trek- Compliant

A symbol of our commitment to sustainable technologies

Storage : Store between +5 °c to 35 °c in original pack, well-sealed & stored.
Shelf-life : Product is stable for 6 months from the date of production / Invoice.



Non flammable

Avoid direct contact with skin



Prevent from freezing

Use Gloves / Ensure Ventilation



Note: Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.