

## SOFTNER ESW

Deep penetrating softener made of new generation polymeric softeners and synthetic oils. It imparts excellent softness and feel to the treated leathers and behaves considerably strong for the upper fabrication. The softener is to be sprayed on the flesh-side of the leathers before assemblage. It improves the tear strength of treated leather and makes the leather water-repellant with soft and silky touch.

- Characteristics :
- New generation polymeric softener
  - Deep penetrating softening agent
  - Improves the tear strength
  - Imparts water-repellant capability

Physical Properties :

Appearance	: Viscous emulsion
Solubility	: Soluble in water
Active %	: 57 ± 2
pH	: 7, 0 ± 0,5 (10% Emulsion)

- Procedure :
- Clean the surface of flesh-side thoroughly
  - Apply **Softner ESW** on the flesh-side by spray / brush
  - Allow time between application and assemblage
  - Must be allowed to dry overnight
  - Can be used even after cutting the components
  - Do not apply on the grain-side (upper side)

Packing : 1 kg in plastic Bottle | 10 kg in plastic Jerrycan | 30 kg in HDPE Drum

Storage : Store between +5° c – 35° c in original pack, well sealed & stored.

Shelf-life : Product is stable for 9 months from the date of production/Invoice.

### REACH Compliant



Non flammable

Store in Shade



Prevent from freezing

Use Gloves / Ensure Ventilation



The technical information and application suggestions presented above are based on company's present knowledge based on careful in - house tests. Since the conditions of use at customer's site are beyond the control of the company, therefore the company cannot be held responsible for any loss to the customer resulting from the use of above products or application suggestions. The company reserves the right to modify the specifications without prior information.