

UREZ 785 M

Characteristics of Emulsion

Appearance	: Milky Emulsion
Nature	: Aliphatic Polyurethane Dispersion
Charge	: Anionic
Solid Content	: 21 ± 1%
pH (10% Sol.)	: 9.0 ± 0.5
N.M.P/ NEP Content (%)	: Nil
Mechanical Stability	: Good

Characteristics of Film

Appearance	: Opaque and Matt
Gloss	: 6 BYK Gardner
Shore A Hardness	: 95 (Zwick/Roell)
Light Fastness	: Excellent
Cold-crack Resistance	: Excellent

REACH COMPLIANT



Green-Trek- Compliant

a symbol of our commitment to sustainable technologies

Storage : Store between +5 °c to 35 °c in original pack, well-sealed.
Shelf-life : Product is stable for 6 months from the date of production.



Non Flammable / Keep Flames Away

Store Indoors



Protect From Snow

Use Gloves/Ensure Ventilation



Matt Polyurethane Dispersion for use as a aqueous top coat for an elegant look and VOC free finishes on leather.

UREZ 785 M is a dull waterborne aliphatic polyurethane dispersion designed for high performance upper and upholstery leather. Treated leathers will have a pleasant, soft and warm handle that fulfils high standards of fastness. The film properties confer good flexibility, excellent rub fastness, perspiration and ageing resistance.

UREZ 785 M can be combined with Urez 785 G for regulating the final gloss on leather. The product can be blended with various feel modifiers to achieve the desired touch. It can be cross-linked with the help of Xama 2 or Xama 7.

Usage

- Matt Top Coat : 900 parts **Urez 785 M**
85 parts Glaze Top N
7 parts Finish M 45
3 parts Leveller 168
5 parts Xama 7
- Low Gloss Top Coat : 500 parts **Urez 785 M**
495 parts Urez 785 G
5 parts Xama 7

IMPORTANT: PROTECT FROM FREEZING.

Note: Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.