

## HARDENER 62

A high penetrating Acrylic Resin emulsion that increases the stiffness of leathers. Imparts excellent hardening effect on the fibre of edges of leather sole and prevents wax from oozing. Performs well when applied on the flesh-side to achieve higher adhesion, better initial tack and resistance against high temperature and plasticizers. Can be used even after cutting the components; followed by ironing and plating.

- Characteristics :
- High penetrating Acrylic Resin emulsion increases the stiffness of leathers
  - Can tolerate high temperature plating
  - Prevents wax from oozing

Physical Properties :

Appearance	: Yellowish transparent liquid
Solubility	: Soluble in water
Active %	: 14 ± 2
pH	: 6.5 ± 0.5 (10% Emulsion)

- Procedure :
- Clean the flesh-side thoroughly
  - Apply **Hardener 62** on the flesh-side by spray / brush
  - Do not apply on the grain-side (upper side)
  - Can be used even after cutting the components
  - Ironing and plating to be followed to improve results

Packing : 1 kg in plastic Bottle | 10 kg in plastic Jerrycan | 30 kg in HDPE Drum

Storage : Store between +5° c – 35° c in original pack, well sealed & stored.

Shelf-life : Product is stable for 9 months from the date of production/Invoice.

### REACH Compliant



Non flammable

Store in Shade



Prevent from freezing

Use Gloves / Ensure Ventilation



The technical information and application suggestions presented above are based on company's present knowledge based on careful in - house tests. Since the conditions of use at customer's site are beyond the control of the company, therefore the company cannot be held responsible for any loss to the customer resulting from the use of above products or application suggestions. The company reserves the right to modify the specifications without prior information.