

## LUCIDO 10061

Aliphatic Polyurethane, aqueous liquid dressing emulsion, used as a special glossy dressing for finishing uppers. It is particularly suitable to obtain excellent clod, crack, abrasion and scuff resistance. It forms a glossy film with a dry, slippery feel. A light final brushing increases sealing effect. Cleaning / degreasing essential before application to prevent lack of adhesion after waxes or silicones.

- Characteristics :
- Aqueous aliphatic Polyurethane coat
  - Imparts excellent cold-flex resistance
  - Forms glossy film with dry, slippery feel
  - Increases sealing effect
  - Works as adhesion promoter
  - Compatible with **Colorante** colors

Physical Properties :

Appearance	: Neutral emulsion
Solubility	: Soluble in water
Active %	: 31 ± 2
Gloss	: High
pH	: 8,0 ± 0,5 (10% emulsion)

- Procedure :
- Clean the surface thoroughly
  - Remove all traces of waxes or silicones on uppers
  - Apply **Lucido 10061** with spray gun or sponge
  - Dry the surface completely
  - Adhesion to be checked after 24 hours.
  - Use **Colorante** for colors
  - Stir well before use

Packing : 1 kg in plastic Bottle | 10 kg in plastic Jerrycan | 30 kg in HDPE Drum

Storage : Store between +5° c – 35° c in original pack, well sealed & stored.

Shelf-life : Product is stable for 9 months from the date of production/Invoice.

### REACH Compliant



Non flammable

Store in Shade



Prevent from freezing

Use Gloves / Ensure Ventilation



The technical information and application suggestions presented above are based on company's present knowledge based on careful in-house tests. Since the conditions of use at customer's site are beyond the control of the company, therefore the company cannot be held responsible for any loss to the customer resulting from the use of above products or application suggestions. The company reserves the right to modify the specifications without prior information.