

SOFTINA A Hydro-Alcoholic solution used for uppers as softening agent before lasting. It prevents cracking of the grain of upper finish when applied on the flesh-side. Its softening compound does not alter grain appearance in any way. Imparts natural softness and suppleness to upper.

- Characteristics :
- Water soluble softening agent for uppers
 - Prevents breaking of the grain
 - Imparts natural softness & suppleness
 - Does not alter the grain appearance

Physical Properties :

Appearance	: Transparent clear fluid
Solubility	: Soluble in water
Active %	: 11 ± 2
pH	: 7.5 ± 0.5 (10% Emulsion)

- Procedure :
- Clean the surface of flesh-side thoroughly
 - Apply **Softina** on the flesh-side by spray
 - Time between application and lasting depends upon the quantity applied
 - Must test the stability of the finish before application
 - General dilution ratio 1:1- can be modified

Packing : 1 kg in plastic Bottle | 10 kg in plastic Jerrycan | 30 kg in HDPE Drum
 Storage : Store between +5° c – 35° c in original pack, well sealed & stored.
 Shelf-life : Product is stable for 9 months from the date of production/invoice.

REACH Compliant



Non flammable

Store in Shade



Prevent from freezing

Use Gloves / Ensure Ventilation



The technical information and application suggestions presented above are based on company's present knowledge based on careful in - house tests. Since the conditions of use at customer's site are beyond the control of the company, therefore the company cannot be held responsible for any loss to the customer resulting from the use of above products or application suggestions. The company reserves the right to modify the specifications without prior information.