

VERNICE OPECA

Solvent based matt lacquer dressing for quick drying and self-shine application. Consists of high quality inorganic matting agent, nitrocellulose solvents, waxes and feel modifiers. Suitable for achieving a matt and silky finish on uppers without graying. Recommended to use as matting auxiliary when mixed with **Vernice Lam** and **Vernice Bianco**.

- Characteristics :
- Matt lacquer spray with solvent
 - Forms matt film on uppers / soles
 - No offensive odor
 - Works as matting agent
 - Confers waxy feel and smoothness
 - Compatible with **Colorante** colors

Physical Properties :

Appearance	: Transparent liquid
Solubility	: Soluble in solvents
Active %	: 5 ± 1
Gloss	: Low
pH	: N.A.

- Procedure :
- Clean the surface thoroughly
 - Apply **Vernice Opeca** with 1 mm conical jet spray nozzle
 - Ideal spraying distance should be 30 cm
 - Adjust spray gun pressure to 3 – 3,5 atm
 - Leave to dry the surface in a dust free atmosphere
 - Compressed air must have low moisture content
 - Use **Colorante** for colors
 - Use **Luber B** for dilution
 - Use **Vernice Lam** or **Vernice Bianco** for reducing matting

Packing : 1 kg in plastic Bottle | 10 kg in plastic Jerrycan | 30 kg in HDPE Drum

Storage : Store between +5° c – 35° c in original pack, well sealed & stored.

Shelf-life : Product is stable for 9 months from the date of production/Invoice.

REACH Compliant



Non flammable

Store in Shade



Prevent from freezing

Use Gloves / Ensure Ventilation



The technical information and application suggestions presented above are based on company's present knowledge based on careful in-house tests. Since the conditions of use at customer's site are beyond the control of the company, therefore the company cannot be held responsible for any loss to the customer resulting from the use of above products or application suggestions. The company reserves the right to modify the specifications without prior information.