



LEATHER FINISH 235

Characteristics	
Appearance	: Very Fine Emulsion
Nature	: PU based resin
Solid Content	: 35 ± 1%
pH (10% Sol.)	: 9.0 ± 0.5
Density	: 1.04
Charge	: Anionic
Gloss	: Medium
Mechanical stability	: Good
Reaction with ammonia	: None

Characteristics of film	
Appearance	: Transparent
Elongation	: 10 (1 Min. - 10 Max.)
Gloss	: 08 (1 Matt -10 Glossy)
Shore Hardness	: 04 (1 Softest - 10 Hardest)
Light Fastness	: Good
Cold-crack Resistance	: Good

REACH COMPLIANT



Green-Trek- Compliant

A symbol of our commitment to sustainable technologies

Storage : Store between +5 'c to 35 'c in original pack, well-sealed.
Shelf-life : Product is stable for 6 months from the date of production.

Medium soft resin finish for leather.

LEATHER FINISH 235 is a medium soft PU based Resin having good water and solvent resistance. The leather may be finished with the product, alone or alongwith other ingredients like pigments, acrylics and waxes It's good anchorage characteristic makes it ideal for use in sophisticated leathers like garments, softies and upholstery.

Usage

- Sheep Garment: 100 parts Pigment – Nano Series
50 parts Glaze Top N
30 parts Wax 16 S
520 parts Water
125 parts Leather Finish 235
75 parts Acril-m M 701
100 parts Urez 899
- Goar Shoe Uppers: 100 parts Pigment – Nano Series
30 parts Protop 18
30 parts Filler WTD
50 parts Filler 12/61
530 parts Water
100 parts Leather Finish 235
100 parts Acril-m S 8/1
50 parts Urez 894
10 parts Liquid NH₃

IMPORTANT: Protect from freezing.
Note: Suggested formulations are only for guidance and necessary modifications must be made to achieve a particular result.



Non Flammable / Keep Flames Away Store Indoors



Protect From Snow Use Gloves/Ensure Ventilation

