

COW FINE MILLED SOFTY/BAG: FULL GRAIN RESIN FINISH: BLACK

FINISHING FORMULATION & PROCESS							
S.No.	PRODUCT	1	2	3	4	5	PROCESS / REMARKS
1	Primer PFR	200					1. 1 X Coat, Dry.
2	Luber 205	50					2. 1 Pad coat, Fine h/c
3	Water	750	580	100	950		at 70°C/ 100Kg./cm ² .
4	Nano Deep Black		70				3X coats.
5	Novolene PR Black		30				3. 2 X coat, Kiss Plate
6	Acril-m X 858		100				at 80°C.
7	Acril-m S 8/1		100				4 4 V anni
8	Glaze Top N		50				4. 1 X coat.
9	Wax 16/S		40				
10	Sensallon W		20				
11	Hicalac 316			100			
12	Finish M 45				50		
13							
14							
15							
16							
17							
18							
19							
20							
21							
22							
23							
24							

APPLICATION:

REMARKS:



Committed to sustainable technologies

REMARKS :

Code:

Po = Polish Polish Po = Polish Po = Polish Po = Polish Polish

Suggested products comply with REACH and free from:

- Heavy Metals, Cr. VI
 AP(APEO, SCCP, Phylinder)
- AP/APEO, SCCP, Phthalate
- Arylamines (Azo group), Forbidden Amines
- PFCs, PAHs, PFOs, PCB
- Formaldehyde, NMP, NEP, DMF
- Complies with VOC emission