

COW NATURAL DRY MILLED: RESIN FINISH: BLACK

FINISHING FORMULATION & PROCESS							
S.No.	PRODUCT	1	2	3	4	5	PROCESS / REMARKS
- 1	Nano Black Super	100					1. 2 Pad Coats, Dry
2	Novolene PR Black	50					well, Fine H/C plate at 70 °C / 100 Kg.
3	Acril-m S 60	50					2 X Coats, Dry well.
4	Acril-m X 01	100					
5	Acril-m M 701	100					2. 2 X Coat, Dry well, Stake, Dry Mill for
6	Neowax ST	50					4 Hrs.
7	Primer PFR	50					O 1 V Cook Chalco 9
8	Protop 18	30					1 X Coat, Stake & Toggle.
9	Luber 205	20					
10	Water	370	150	750			
11	Hicalac 312		100				
12	Modifier CA/2			175			
13	Finish M 45			75			
14	Uphin 100	100					
15							
16							
17							
18							
19							
20							
21							
22							
23							
24							

APPLICATION:

REMARKS:



Committed to sustainable technologies

REMARKS :

Code:

Po = Polish P = Plate $^{\circ}$ C/Bar M = Dry Drum (Mill) Pr = Emboss $^{\circ}$ C RB = Rebuff Vd = Vacuum Dry O/N = Over Night

Suggested products comply with REACH and free from:

- Heavy Metals, Cr. VI
 AP(APEO, SCCP, Phylinder)
- AP/APEO, SCCP, Phthalate
- Arylamines (Azo group), Forbidden Amines
- PFCs, PAHs, PFOs, PCB
- Formaldehyde, NMP, NEP, DMF
- Complies with VOC emission