

FINISHING FORMULATION & PROCESS							
S.No.	PRODUCT	1	2	3	4	5	PROCESS / REMARKS
1	Urez 899	150	50				 1 X Coat, plate at 80° C, 50 Kg./cm². 4 X Coats, Dry well, plate at 80°C, 50 Kg./cm².
2	Protop SP	50					
3	Novolene PR Dyes	50	40				
4	Water	750	600	790			
5	Pigment - Nano Series		30				
6	GlazEx 72		100				3. 2 X Coat, dry well,
7	Glaze Top N		100				Fix with crosslinker or formalin, plate at 90°C, 50 Kg./cm ² ., toggle.
8	Glaze Top EC		50	100			
9	Luber 150		30				
10	Glaze Top LM 58			100			
11	Crosslinker		3	5			
12	Finish M 45			5			
13							
14							
15							
16							
17							
18							
19							
20							
21							
22							
23							
24							

SHEEP NAPPA-2 : CASEIN FINISH : FLAME RED

APPLICATION :

REMARKS:



Suggested products comply with REACH and free from:

- Heavy Metals, Cr. VI
- AP/APEO, SCCP, Phthalate
- Arylamines (Azo group), Forbidden Amines
- PFCs, PAHs, PFOs, PCB
- Formaldehyde, NMP, NEP, DMF
- Complies with VOC emission