

| FINISHING FORMULATION & PROCESS | | | | | | | |
|---------------------------------|-----------------------------|-----|-----|-----|-----|---|--|
| S.No. | PRODUCT | 1 | 2 | 3 | 4 | 5 | PROCESS / REMARKS |
| | | | | | | | |
| 1 | Filler KT | 50 | | | | | 1. 2 X Coat, Dry well, |
| 2 | Cationic Black Dye Solution | 50 | | | | | Kiss plate. |
| 3 | Black 33 KT | 30 | | | | | 2. 3 X Coats, Dry well. |
| 4 | Celina 34 KT | 30 | | | 100 | | |
| 5 | Brillento 91 KT | 100 | | | | | 2 X Coat, Dry well, Dry Shave, Contilux. |
| 6 | PUD 48 KT | 100 | | | | | |
| 7 | Finish M 45 | 20 | | 5 | 50 | | 4. 1 X Coat, Stake, |
| 8 | Luber 150 | 20 | 10 | | | | Dry Mill for 30 min. and Toggle. |
| 9 | Water | 600 | 510 | 95 | 850 | | |
| 10 | Nano Black Super | | 80 | | | | |
| 11 | Novolene PR Black | | 20 | | | | |
| 12 | Acril-m M 701 | | 50 | | | | |
| 13 | Acril-m X 858 | | 100 | | | | |
| 14 | Acril-m S 8/1 | | 50 | | | | |
| 15 | Urez 899 | | 100 | | | | |
| 16 | Glaze Top N | | 30 | | | | |
| 17 | Filler 50 | | 50 | | | | |
| 18 | Hicalac 312 | | | 100 | | | |
| 19 | | | | | | | |
| 20 | | | | | | | |
| 21 | | | | | | | |
| 22 | | | | | | | |
| 23 | | | | | | | |
| 24 | | | | | | | |

SHEEP - NEW ZEALAND - GARMENT NAPPA : RESIN FINISH : BLACK

APPLICATION :

REMARKS:



Suggested products comply with REACH and free from:

- Heavy Metals, Cr. VI
- AP/APEO, SCCP, Phthalate
- Arylamines (Azo group), Forbidden Amines
- PFCs, PAHs, PFOs, PCB
- Formaldehyde, NMP, NEP, DMF
- Complies with VOC emission